

Thermo Scientific
Dionex UltiMate 3000
Electrochemical Detector



Redefining electrochemical detection

Sensitivity • Selectivity • Optimized Performance

UHPHLC⁺
focused


Thermo
SCIENTIFIC

Higher sensitivity greater selectivity

The Thermo Scientific™ Dionex™ UltiMate™ 3000 electrochemical detector, designed by the pioneers of coulometric electrochemical detection, delivers state-of-the-art sensor technologies complete with an entire range of high performance and ultra-high performance LC systems optimized for electrochemical detection.

For today's researcher, there is a continuing need for detecting vanishingly small quantities of analyte and often in complex samples. Because electrochemical detection measures only compounds that can undergo oxidation or reduction it is both highly sensitive and very selective.

- Direct measurement to femtogram levels
- Very low sample volume requirement
- Readily eliminates matrix interferences
- Selectively detects analytes of interest



Improved temporal resolution in microdialysis experiments with UHPLC

Electrochemical detection delivers

high sensitivity for neurotransmitter analysis, simplicity and robustness for pharmaceutical or clinical diagnostics, and the selectivity for the characterization of complex samples such as natural products, biological tissues and fluids.

Take it to the next level

The UltiMate 3000 ECD-3000RS takes electrochemical detection to the next level with UHPLC compatibility and total system integration, all with unprecedented operational simplicity.

- Choice of sensors – both coulometric and amperometric sensors to meet the demands of any application
- UHPLC compatibility – ultralow peak dispersion and high data acquisition rates for conventional or fast, high resolution chromatography
- Modular – easily expandable to multiple independent sensors for unrivaled flexibility
- Gradient compatibility – the only electrochemical detector capable of operating aggressive gradients for method flexibility
- Autoranging – simultaneously measure both low and high levels of analytes without losing data
- SmartChip™ technology – easy operation with automatic sensor recognition, event logging and electrode protection



pharmaceutical clinical research food and beverage
neuroscience natural products metabolomics
clinical diagnostics oxidative stress botanicals

SmartChip sensors make the difference

Introducing SmartChip Technology

The next generation of electrochemical sensors have arrived—all sensors for the ECD-3000RS detector have built-in SmartChip technology:



- Automatic recognition – identifies installed sensor model type and defines data channels in Thermo Scientific Dionex Chromeleon™ chromatography data system software
- Audit trail logging – records sensor diagnostics making it ideal for GMP/GLP reporting
- Integrated sensor protection – selects the allowable potential for the sensor and working electrode material

Choose from amperometric and coulometric sensors

Amperometric sensors are chosen when an application demands high sensitivity measurement especially when sample volumes are limited. Coulometric sensors, unique to Thermo Fisher Scientific, are the sensors of choice to maximize both selectivity and sensitivity.

The amperometric Thermo Scientific Dionex 6041RS ultra analytical sensor

- Optimized for high sensitivity
- Compatible with column formats from microbore to conventional 4.6 mm diameters
- HPLC and UHPLC compatible
- Available with a variety of working electrode materials, including boron-doped diamond (BDD)
- Maintenance-free solid state reference electrodes for long-term stability and reliability
- Easy assembly with new ratcheted design





The Thermo Scientific Dionex 6011RS dual electrode coulometric sensor

This sensor has flow-through graphite electrodes that provide near 100% efficiency, independent of flow rate. This reliable, general purpose sensor is maintenance-free for routine analysis with minimal downtime.


- Dual, independent electrode design for selective analysis
- Identify and resolve co-eluting analytes
- Ultra-low internal volume for HPLC and UHPLC compatibility
- Maintenance-free, solid-state reference electrodes for stability and reliability
- The industry standard for reliable electrochemical detection

Coulometric electrodes offer more than just sensitivity. A distinct advantage is realized by manipulation using two coulometric electrodes in series. In screen mode, the high efficiency of the first electrode removes interferences, leaving the second electrode free to selectively measure the analytes without the need for complex sample preparation. This even allows for the resolution of co-eluting analytes.

In RedOx mode, the inherent electrochemical properties of some analytes can be used to further enhance the selectivity. The result is better quantitation—free from interferences.



Epinephrine (E) and Octopamine (OA) are unresolved using an amperometric sensor (Figure A).




With a dual coulometric sensor Epinephrine (E) and Octopamine (OA) are electrochemically resolved (Figure B).

Optimized for simplicity and performance

Operational Simplicity™ with Chromeleon software

The ECD-3000RS detector is controlled by Chromeleon chromatography data software. Using Operational Simplicity as its guiding design principle, Chromeleon 7 takes you from samples to results in the shortest time possible.

- Fully integrated with SmartChip Technology
- COBRA signal processing for automatic peak recognition
- SmartPeaks assistant recommends best available integration solution to individual or multiple chromatograms
- Streamline and automate the chromatography process from injection to final report using eWorkflows
- Seamless integration and access to the online electrochemical applications and methods library



The screenshot displays the Chromeleon 7 software interface, specifically the 'Data' section. It shows a table with columns for Name, Type, Date Modified, and Comment. The table lists several data points, including 'acetaminophen_68' and 'acetaminophen_69'. The interface also includes a sidebar with various toolbars and a top menu bar.

Name	Type	Date Modified	Comment
acetaminophen_68	Instrument Method	5/3/2011 2:44 PM	for standard 36 wellplates
acetaminophen_69	Instrument Method	5/3/2011 2:44 PM	for standard 96 wellplates
acetaminophen_70	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_71	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_72	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_73	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_74	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_75	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_76	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_77	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_78	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_79	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_80	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_81	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_82	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_83	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_84	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_85	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_86	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_87	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_88	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_89	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_90	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_91	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_92	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_93	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_94	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_95	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_96	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_97	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_98	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_99	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates
acetaminophen_100	Instrument Method	5/3/2011 2:44 PM	for standard 96 deep wellplates

Thermo Scientific UltiMate 3000 UHPLC+ Systems Optimized for Electrochemical Detection

Maximum performance comes not just from the detector but also from its integration with an LC system designed for electrochemical detection. UltiMate 3000 UHPLC+ systems set a new standard of robustness, durability and performance. The EC-optimized line of LC systems provide an inert fluidic flow-path that minimizes noise and unwanted auto-oxidation.

- Pumps and autosamplers designed to achieve the lowest possible electrochemical noise
- SmartFlow™ pump technology for zero pulse delivery, perfect for high sensitivity applications
- Autosampler with flow-through injection technology for sample loss, ideal when sample volume is limited

The EC-compatible nanoViper fitting system provides fingertight, zero-dead-volume connections for any column, at any flow rate, for any valve, and any pressure up to 1000 bar. Its elegant design ensures easy connection of all fluidics for every operator experience level



www.thermofisher.com/ECdetection

©2016 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

Australia +61 3 9757 4486
Austria +43 1 616 51 25
Benelux +31 20 683 9768
+32 3 353 42 94
Brazil +55 11 3731 5140

China +852 2428 3282
Denmark +45 36 36 90 90
France +33 1 39 30 01 10
Germany +49 6126 991 0
India +91 22 2764 2735

Ireland +353 1 644 0064
Italy +39 02 51 62 1267
Japan +81 6 6885 1213
Korea +82 2 3420 8600
Singapore +65 6289 1190
Sweden +46 8 473 3380

Switzerland +41 62 205 9966
Taiwan +886 2 8751 6655
UK +44 1276 691722
USA and Canada +847 295 7500

Thermo
S C I E N T I F I C
Part of Thermo Fisher Scientific